

AS752VET

Coagulation Analyzer



FEATURES

AS752VET

Coagulation Analyzer

General Features

Parameters: PT, APTT, TT, FIB, etc.
Principle: Clotting, optical method
Disposable cuvette, no carry-over
Precise electronic pipette
Languages: English, French, Spanish, Portuguese, etc.
Automatic start at reagent addition
Thermal printer, auto&manual print
Support LIS
Less and easy maintenance

2 independent channels
Display: 5-inch screen
Cuvette incubation positions: 12
Reagent incubation positions: 5
Size: 345mm x 255mm x 145mm
Net weight: 4.4kg

Technical Specifications

Wavelength: LED 470nm
Memory: 10,000 results storage
Input: Keypad
Sample volume: 20-40µL
Reagent volume: 20-40µL
Electronic pipette: 20-200µL
Available dimensions: Seconds, mg/dL, g/L, U/L
Incubation temperature: 37.0±1.0°C
Relative humidity: ≤85%
Precision: PT, APTT, FIB ≤ 5%; TT ≤ 8% (Normal sample)
Deviation between channels: ≤ 5%
Power supply: AC 100-240V 50/60Hz
CE marked



ASSEL S.r.l.

Add: Via E. Barsanti, 8-13/A Guidonia-Montecelio 00012 (RM)
Tel: 0774.357492 - 0774.374176 Fax: 0774.372179 - 0774.379190
Email: info@asselitaly.eu Website: www.asselitaly.eu

